


## Needle roller bearing NA4910-U-IKO - NA4910-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na4910-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
50	—	NA 4910U	—	—	295	50	72	22	23
$r_s$ min	Standard mounting dimensions mm		Basic rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring			
0.6	Min. 58 Max. 54	Max. 57 Min. 68	N 41 300	N 71 100	3 500	LRTZ 505823			

Notes: (1) Minimum allowable value of diameter dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381589
Inside diameter	50 mm
Outside diameter	72 mm
Thickness	23 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE