

## Needle roller bearing NA6913-U-IKO - NA6913-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na6913-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
65	—	—	—	—	NA 6913U	845	65	90	45	46

r <sub>s</sub> min (1)	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.			
1	72	70	70.5	85	97 400	200 000	LRTZ 657246

Notes: (1) Minimum allowable value of diameter dimension r  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381718
Inside diameter	65 mm
Outside diameter	90 mm
Thickness	46 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE