

Needle roller bearing NA6914-UU-IKO - NA6914-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na6914-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.)	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		ϕ	d	D	C
70	—	—	NA 6914UU	—	1 400	70	100	54	55

r_s min	F_w	Standard mounting dimensions mm			Basic static load rating C_0	Basic dynamic load rating N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
		Min.	Max.	d_s				
1	80	75	78	95	124 000	281 000	2 500	LRTZ 709055

Notes: (1) Minimum allowable value of diameter dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381763
Inside diameter	70 mm
Outside diameter	100 mm
Thickness	55 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE