

## Needle roller bearing NA6916-UU-IKO - NA6916-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na6916-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
<b>80</b>	—	—	<b>NA 6916UU</b>	—	1 570	80	110	54	55

r <sub>s</sub> min (°)	F <sub>w</sub>	Standard mounting dimensions mm			Basic static load rating C <sub>0</sub> N	Basic dynamic load rating C <sub>10</sub> N	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
		d <sub>s</sub> Min.	d <sub>s</sub> Max.	D <sub>s</sub> Max.				
1	90	85	88	105	132 000	317 000	2 000	LRTZ 809055

Notes: (1) Minimum allowable value of chamfer dimension r  
 (2) Allowable rotational speed applies to grease lubrication.  
 Remark: The outer ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381848
Inside diameter	80 mm
Inside diameter	3.15" inch
Outside diameter	110 mm
Outside diameter	4.331" inch
Thickness	55 mm
Thickness	2.165" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE