

Needle roller bearing NA4917-U-IKO - NA4917-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na4917-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
85	—	NA 4917U	—	—	1 300	85	120	35	36

r _s mm ⁽¹⁾	F _w	Standard mounting dimensions mm		Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring		
		d _s Min.	d _s Max.					
1.1	100	91.5	98	113.5	103 000	225 000	1 900	LRTZ 8510036

Notes: (1) Minimum allowable value of diameter dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381862
Inside diameter	85 mm
Outside diameter	120 mm
Thickness	36 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE