


Needle roller bearing NA4918-UU-IKO - NA4918-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/na4918-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals		With one seal	d	D	C	B
90	NA 4918UU	—	—	—	1 360	90	125	35	36

r _s min ⁽¹⁾ F _w	Standard mounting dimensions mm		Basic static load rating C ₀	Basic dynamic load rating C ₁₀	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 9010536
	Min.	Max.				
1.1	105	96.5 103	118.5	106 000	238 000	1 800

Notes: (1) Minimum allowable value of outer diameter r
(2) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381893
Inside diameter	90 mm
Outside diameter	125 mm
Thickness	36 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE