


Needle roller bearing BR122016-U-IKO - BR122016-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/br122016-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
19.050 ($\frac{3}{4}$)	BR 122016 U		68	19.050 ($\frac{3}{4}$)	31.750 (1 $\frac{1}{4}$)	25.400 (1)
Standard mounting dimensions mm		Basic dynamic load rating C	Static load rating C_0	Allowable rotational speed ^(*)		
D_1 Max.	r_{as} max (⁽¹⁾)	N	N	rpm		
26.5	1.0	20 700	24 400	10 000		

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
^(*) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382104
Inside diameter	19.05 mm
Outside diameter	31.75 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE