


Needle roller bearing BR243320-U-IKO - BR243320-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/br243320-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
38.100 (1 1/2)		BR 243320 U	168	38.100 (1 1/2)	52.388 (2 1/4)	31.750 (1 1/4)
Standard mounting dimensions mm		Basic dynamic load rating C	Static load rating C_0	Allowable rotational speed ^(*)		
D_1	$r_{as \text{ max}}$ ^(†)	N	N	rpm		
45.1	1.5	43 700	66 900	5 500		

Note⁽¹⁾ Minimum allowable value of chamfer dimension r
^(†) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382227
Inside diameter	38.1 mm
Outside diameter	52.388 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE