


## Needle roller bearing BRI122416-U-IKO - BRI122416-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bri122416-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
<b>19.050</b> (3/4)		<b>BRI 122416 U</b>	127	19.050 (3/4)	38.100 (1 1/2)	25.400 (1)	25.650	
F <sub>w</sub>	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring		
	Min.	Max.				Min.	Max.	
25.400 (1)	24	24.4	32.9	0.6	23 600	31 300	8 000	<b>LRBZ 121616 B</b>

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication.  
Remark: This roller ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382524
Inside diameter	19.05 mm
Outside diameter	38.1 mm
Thickness	25.4 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE