

## Needle roller bearing BRI223520-U-IKO - BRI223520-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bri223520-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
<b>34.925</b> (1 3/8)		<b>BRI 223520 U</b>	275	34.925 (1 3/8)	55.562 (2 1/8)	31.750 (1 1/4)	32.000
$F_w$	Standard mounting dimensions (mm)			Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring LRBZ 222620 B
	Min.	Max.	Max. as max. <sup>(*)</sup>				
	40.2	40.2	48.3	44 800	70 900	4 500	

Notes: (\*) Minimum allowable value of chamfer dimension r.  
(\*\*) Allowable rotational speed applies to grease lubrication.  
Remark: The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382630
Inside diameter	34.925 mm
Outside diameter	55.562 mm
Thickness	31.75 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE