


Needle roller bearing BRI365628-UU-IKO - BRI365628-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bri365628-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)			
	With two seals	With one seal		d	D	C	B
57.150 (2 1/4)	BRI 365628 UU		980	57.150 (2 1/4)	88.900 (3 1/2)	44.450 (1 3/4)	44.700
F_w	Standard mounting dimensions (mm)		Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
	Min.	Max.				Min.	Max.
69.850 (2 3/4)	65	67	98 700	189 000	2 500	LRBZ 364428 B	

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382746
Inside diameter	57.15 mm
Outside diameter	88.9 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE