


Needle roller bearing BRI365628-U-IKO - BRI365628-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bri365628-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



| Shaft dia. mm (inch) | Identification number | | Mass (Ref.) g | Boundary dimensions mm(inch) | | | | |
|----------------------------|-----------------------------------|---------------------|---------------------------------|-------------------------------------|---|--|----------------------|---------------|
| | With two seals | With one seal | | d | D | C | B | |
| 57.150 (2 1/4) | | BRI 365628 U | 980 | 57.150 (2 1/4) | 88.900 (3 1/2) | 44.450 (1 3/4) | 44.700 | |
| F_w | Standard mounting dimensions (mm) | | | Basic dynamic load rating C N | Basic static load rating C ₀ N | Allowable rotational speed ^(*) rpm | Assembled inner ring | |
| | Min. | Max. | Misg. as max. ^(*) | | | | | |
| 69.850 (2 3/4) | 65 | 67 | 80.7 | 1.5 | 98 700 | 189 000 | 2 500 | LRBZ 364428 B |

Notes: (*) Minimum allowable value of diameter dimension r.
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952382753 |
| Inside diameter | 57.15 mm |
| Outside diameter | 88.9 mm |
| Thickness | 44.45 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE