


Needle roller bearing BRI487232-UU-IKO - BRI487232-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/bri487232-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)				
	With two seals	With one seal		d	D	C	B	
76.200 (3)	BRI 487232 UU		1 738	76.200 (3)	114.300 (4 1/2)	50.800 (2)	51.050	

F _w	Standard mounting dimensions (mm)			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm	Assembled inner ring LRBZ 485632 B
	Min.	Max.	Max. as max. ^(*)				
88.900 (3 1/2)	83.5	86	106.1	142 000	265 000	2 000	LRBZ 485632 B

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382814
Inside diameter	76.2 mm
Outside diameter	114.3 mm
Thickness	50.8 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE