

Needle roller bearing GBR202820-UU-IKO - GBR202820-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbr202820-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
31.750 (1.250)	GBR 202820 UU		152	31.750 (1.250)	44.450 (1.750)	31.750 (1.250)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball dynamic load rating C_0	Allowable rotational speed ^(*)		
D_A	r as max	N	N	rpm		
Max.	0.6	46 600	83 900	2 500		

Notes: (*) Minimum allowable value of diameter dimension r
(**) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952382951
Inside diameter	31.75 mm
Outside diameter	44.45 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE