


Needle roller bearing GBR526828-UU-IKO - GBR526828-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbr526828-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With 6/8e seal		F_w	D	C
82.550 (3 1/4)	GBR 526828 UU		960	82.550 (3 1/4)	107.950 (4 1/4)	44.450 (1 3/4)
Standard mounting dimensions mm		Seal dynamic load rating C	Ball/cage dynamic load rating C_0	Allowable rotational speed ^(*)		
D_A Max.	r as max (^(†))	N	N	rpm		
99.9	1.5	127 000	231 000	950		

Notes: (*) Minimum allowable value of diameter dimension r
(†) Allowable rotational speed applies to grease lubrication.
Remark: The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383170
Inside diameter	82.55 mm
Outside diameter	107.95 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE