

Needle roller bearing GBR567232-U-IKO - GBR567232-U-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbr567232-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		F_w	D	C
88.900 (3 1/2)	GBR 567232 U		1 240	88.900 (3 1/2)	114.300 (4 1/2)	50.800 (2)
Standard mounting dimensions mm		Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*) rpm		
D_s Max.	$r_{s \text{ max}}$	N	N			
106.3	1.5	170 000	347 000	900		

Notes: (*) Minimum allowable value of chamber dimension r
(*) Allowable rotational speed applies to grease lubrication.
Remark: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383194
Inside diameter	88.9 mm
Inside diameter	3 1/2" inch
Outside diameter	114.3 mm
Outside diameter	4 1/2" inch
Thickness	50.8 mm
Thickness	2" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE