

Needle roller bearing GBRI142620-UU-IKO - GBRI142620-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbri142620-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series

Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		d	D	C
22.225 (7/8)	GBRI 142620 UU		200	22.225 \pm 0.010	41.275 \pm 0.010	31.750 \pm 0.010

B	F _w	Standard mounting dimensions - mm			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRBZ 141820	
		Min.	Max.	r _{as max} ⁽¹⁾					
32.000	28.575 \pm 0.010	27	27.5	36.3	0.6	43 900	75 300	3 000	LRBZ 141820

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383354
Inside diameter	22.225 mm
Inside diameter	7/8" inch
Outside diameter	41.275 mm
Outside diameter	1 5/8" inch
Thickness	31.75 mm
Thickness	1 1/4" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE