


Needle roller bearing GBR1284828-UU-IKO - GBR1284828-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/gbr1284828-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)					
	With two seals	With one seal		d	D	C			
44.450 (1.75)	GBR1 284828 UU		860	44.450 (1.75)	76.200 (3.0)	44.450 (1.75)			
B	F _w	Standard mounting dimensions mm			Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min.	Max.	D _s Max.					r _{as max} ⁽¹⁾
44.700	57.150 (2.25)	52.5	55	69.2	1.5	87 500	161 000	1 400	LRBZ 283628

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383514
Inside diameter	44.45 mm
Outside diameter	76.2 mm
Thickness	44.45 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE