

Needle roller bearing RNAFW253732-IKO - RNAFW253732-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/rnafw253732-iko>

IKO
NEEDLE ROLLER BEARINGS WITH SEPARABLE CAGE
Without inner ring

| Shaft dia. mm | Identification number | Mass (Ref.) g | Boundary dimensions mm | | | | Standard mounting dimensions mm | | | Basic dynamic load rating C N | Basic static load rating C ₀ N |
|------------------|-----------------------|---------------------|------------------------|----|----|--|---------------------------------|------------------------|----------------|-------------------------------------|---|
| | | | F _w | D | C | r ⁽¹⁾ r _{s min} | d _b | D _s Max. | D _b | | |
| 25 | RNAFW 253732 | 114 | 25 | 37 | 32 | 0.3 | 30.4 | 35 | 25.6 | 33 200 | 49 000 |

Allowable rotational speed⁽²⁾
rpm
20 000

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remark: This roller ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952383965 |
| Inside diameter | 25 mm |
| Outside diameter | 37 mm |
| Thickness | 32 mm |
| Packaging | 1 |

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE