

## Needle roller bearing NAU4900-IKO - NAU4900-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nau4900-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings  
Full Complement Roller Bearings

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> F <sub>s</sub> min	J	E <sub>w</sub>
10	—	NAU 4900	24.5	10	22	13	0.3	15.5	18.5
Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(2)</sup>							
N	N	rpm							
6 580	6 470	30 000							

Note<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
 Note<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
 Remark: This roller ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952385129
Inside diameter	10 mm
Outside diameter	22 mm
Thickness	13 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE