

Needle roller bearing NAU4922-IKO - NAU4922-IKO


<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nau4922-iko>

IKO

ROLLER BEARINGS

Caged Roller Bearings

Full Complement Roller Bearings



NAU49 TRU

Shaft dia. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm					
	Full complement type	Caged type		d	D	C	⁽¹⁾ r _s min	J	E _w
110	—	NAU 4922	—	1 930	110	150	40	1.5	123 138.5
Basic dynamic load rating C									
N									
113 000									
Basic static load rating C ₀									
N									
200 000									
Allowable rotational speed ⁽²⁾									
rpm									
3 500									

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r

⁽²⁾ Minimum rotational speed applies to grease lubrication.

Remark¹ The outer ring has an oil groove and an oil hole.

2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952385730
Inside diameter	110 mm
Outside diameter	150 mm
Thickness	40 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE