


## Needle roller bearing TRU153320-UU-IKO - TRU153320-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/tru153320-uu-iko>

**IKO**  
**ROLLER BEARINGS**  
Caged Roller Bearings [With Seal]  
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r <sup>(1)</sup> min	J
15	—	TRU 153320UU	80.5	15	33	20	0.3	19.5
<i>E<sub>w</sub></i>	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed n <sub>g</sub> rpm					
27	10 400	10 400	9 500					

Notes: (1) Minimum allowable value of chamfer dimension r.  
(\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952385853
Inside diameter	15 mm
Inside diameter	0.591" inch
Outside diameter	33 mm
Outside diameter	1.299" inch
Thickness	20 mm
Thickness	0.787" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE