

## Needle roller bearing TRU405930-UU-IKO - TRU405930-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/tru405930-uu-iko>

**IKO**

**ROLLER BEARINGS**

Caged Roller Bearings **[With Seal]**

Full Complement Roller Bearings **[With Seal]**

NAU49-UU  
TRU-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r <sup>(1)</sup> min	J
40	---	TRU 405930UU		265	40	59	30	0.6	45
<i>E<sub>w</sub></i>	N	N							
52.5	34 700	62 500	4 000						

Notes: (1) Minimum allowable value of chamfer dimension r  
(\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAU and NAI series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386034
Inside diameter	40 mm
Outside diameter	59 mm
Thickness	30 mm
Weight	270 g
Packaging	-
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE