

## Needle roller bearing NAS5017-UU-NR-IKO - NAS5017-UU-NR-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nas5017-uu-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
<b>85</b>	<b>NAS 5017UUNR</b>		2.80	85	130	134.5	60	59	48	5.5

  

f	c	r <sub>s</sub> mm	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm
2.5	2	0.6	101	257 000	446 000	1 200

Notes: (\*) Minimum allowable value of chamfer dimension r  
(\*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.

Remarks: 1. The bearings with seals are provided with prepacked grease.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386928
Inside diameter	85 mm
Inside diameter	3.346" inch
Outside diameter	130 mm
Outside diameter	5.118" inch
Thickness	60 mm
Thickness	2.362" inch
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE