


Needle roller bearing NAS5030-ZZ-NR-IKO - NAS5030-ZZ-NR-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nas5030-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
150		NAS 5030ZZNR	13.5	150	225	233.4	100	99	81	9

f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
3	3.5	1	176.5	629 000	1 210 000	650

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952387079
Inside diameter	150 mm
Inside diameter	5.906" inch
Outside diameter	255 mm
Outside diameter	10.039" inch
Thickness	100 mm
Thickness	3.937" inch
Weight	13500 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE