


Needle roller bearing NAS5072-UU-IKO - NAS5072-UU-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nas5072-uu-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Shafts



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
360	NAS 5072UU		190	360	540	—	243	241	—	—

f	c	r _s mm ⁽¹⁾	J	Basic dynamic load rating C N	Static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm
—	6	2.5	423	3 420 000	7 940 000	250

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952387345
Inside diameter	360 mm
Outside diameter	540 mm
Thickness	243 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE