

Needle roller bearing NBX6040-IKO - NBX6040-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nbx6040-iko>

IKO

COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing Without Inner Ring
Needle Roller Bearings with Thrust Roller Bearing Without Inner Ring

Identification number														
Shaft dia. mm	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g								
60	---	---	---	NBX 6040		501								
Boundary dimensions mm														
F_w	D	D_1	D_2	L	H	r_1 min.	d_f	Basic load rating C	Basic static load rating C_0	Allowable rotational speed ⁽²⁾				
60	72	85	86.5	40	17	12	1	60	82	47 500	64 600	103 000	224 000	4 000

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.

Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390536
Inside diameter	60 mm
Outside diameter	72 mm
Thickness	40 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE