

Needle roller bearing NAXI923-IKO - NAXI923-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/naxi923-iko>

LINEAR TYPE NEEDLE ROLLER BEARINGS

Needle Bearings with Thrust Ball Bearing With Inner Ring
Needle Bearings with Thrust Roller Bearing With Inner Ring

Identification number

	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	d
NAXI 923	49.5	—	—	—	—	—	9

Boundary dimensions mm		Bore diameter mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assemble
B	H			Radial	Radial		
16	9	6.5	9 250	11 200	11 100	9 000	LRT

(1) Minimum allowable value of chamfer dimension r. Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in IAX series, and a maximum of 25% of this value is allowable in the NEX series. The outer ring has an oil groove and an oil hole. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390666
Inside diameter	9 mm
Outside diameter	21 mm
Thickness	23 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE