

Needle roller bearing NAXI1223-IKO - NAXI1223-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/naxi1223-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
12	NAXI 1223	55.5	—	—	—	—	12	24	28

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
D ₂	L	B	H		Radial	Axial			
25	23	16	9	8 230	10 000	9 190	11 100	9 500	LRT 71016

Notes:
 (1) Minimum allowable value of chamfer dimension r.
 (2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
 Remark 1: The outer ring has an oil groove and an oil hole.
 2: Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390680
Inside diameter	12 mm
Outside diameter	24 mm
Thickness	23 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE