


## Needle roller bearing NAXI1223Z-IKO - NAXI1223Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/naxi1223z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring



Shaft dia. mm	Identification number										d	D	D <sub>1</sub>					
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover								
12	<b>NAXI 1223Z</b>										56.5	—	—	—	—	12	24	28

Boundary dimensions mm										Basic dynamic load rating C		Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring LRT		
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sub>max</sub>	r <sub>min</sub>	d <sub>4</sub>	d <sub>5</sub>	d	Radial	Axial	Radial	Axial				
25	23	16	9	6.5	0.3	0.2	10	10	18	9	8	230	10 000	9 190	11 100	9 500	<b>LRT 71016</b>

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390697
Inside diameter	12 mm
Outside diameter	24 mm
Thickness	23 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE