

# Needle roller bearing NAXI1425Z-IKO - NAXI1425Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/naxi1425z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>1</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
14		<b>NAXI 1425Z</b>	65.5	---	---	---	14	26	30

  

Boundary dimensions mm				Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring							
D <sub>2</sub>	L	B	H		Radial	Axial			Radial	Axial					
31	25	17	9	8	0.3	0.3	17	25	18	12 900	10 800	16 300	14 500	8 500	LRT 141717

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimension r  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390734
Inside diameter	14 mm
Outside diameter	26 mm
Thickness	31 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE