

Needle roller bearing NBXI1730Z-IKO - NBXI1730Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nbxi1730z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Shaft dia. mm	Identification number										d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g							
17	---	---	---	---	---	NBXI 1730Z				111	17	30	35

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
D ₂	L	B	H	I ₁	r _{max}	r _{min}	d ₄	d ₅	d		Radial	Axial			Radial
36	30	20.5	10	10.5	0.3	0.3	20	33	19	17 600	19 000	25 400	48 700	11 000	LRT 172020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390796
Inside diameter	17 mm
Outside diameter	30 mm
Thickness	30 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE