

## Needle roller bearing NAXI2530-IKO - NAXI2530-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/naxi2530-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring  
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Shaft dia. mm	Identification number						d	D	D <sub>i</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover	Mass (Ref.) g	With dust cover			
25	<b>NAXI 2530</b>	179	—	—	—	—	25	42	47

Boundary dimensions mm										Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring						
D <sub>2</sub>	L	B	H	I <sub>1</sub>	r <sub>max</sub>	r <sub>min</sub>	d <sub>4</sub>	d <sub>5</sub>	d		Radial	Axial			Radial	Axial				
48	30	20.5	11	9.5	0.6	0.3	30	40	29	25	100	20	400	40	100	33	600	6	500	<b>LRT 253020</b>

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Grease is not prepacked. Perform proper lubrication.

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390840
Inside diameter	25 mm
Outside diameter	42 mm
Thickness	30 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE