

Needle roller bearing NBXI3532-IKO - NBXI3532-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nbxi3532-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D ₁
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
35	---	---	---	NBXI 3532	286	---	35	52	60

Boundary dimensions mm			Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring							
D ₂	L	H			Radial	Radial			Axial						
61	32	20	13	10	0.6	0.3	40	57	39	29 400	41 700	54 100	133 000	6 000	LRT 354020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390949
Inside diameter	35 mm
Outside diameter	52 mm
Thickness	32 mm
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE