

Needle roller bearing NBXI3532Z-IKO - NBXI3532Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nbxi3532z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Shaft dia. mm	Identification number										d	D	D _i	
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g	NBXI 3532Z							294
35	---	---	---	---	---	---	NBXI 3532Z				294	35	52	60

Boundary dimensions mm				Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring			
D ₂	L	B	H			Radial	Radial			Axial		
61	32	20	13	10	57	39	29 400	41 700	54 100	133 000	6 000	LRT 354020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390956
Inside diameter	35 mm
Inside diameter	1.378" inch
Outside diameter	52 mm
Outside diameter	2.047" inch
Thickness	32 mm
Thickness	1.26" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE