

Needle roller bearing NBXI4535Z-IKO - NBXI4535Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/nbxi4535z-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing With Inner Ring
Needle Roller Bearings with Thrust Roller Bearing With Inner Ring

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
45	---	---	---	NBXI 4535Z		396	45	62	70

Boundary dimensions mm			Lead-in chamfer mm	Basic dynamic load rating C	Basic static load rating C ₀		Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring LRT 455025											
D ₂	L	H			Radial	Radial			Axial										
71.5	35	25	14	10	0.6	0.3	50	67	49	42	200	43	300	83	400	148	000	5	000

Notes: (1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NBX series.
Remarks: Z: The outer ring has an oil groove and an oil hole.
2: Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391038
Inside diameter	45 mm
Inside diameter	1.772" inch
Outside diameter	62 mm
Outside diameter	2.441" inch
Thickness	35 mm
Thickness	1.378" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE