

# Needle roller bearing NAXI5040Z-IKO - NAXI5040Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/needle/naxi5040z-iko>

**IKO**  
**COMBINED TYPE NEEDLE ROLLER BEARINGS**

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**  
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D <sub>i</sub>
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
50	<b>NAXI 5040Z 619</b>						50	72	85

  

Boundary dimensions mm				Bore diameter mm	Basic dynamic load rating C	Basic static load rating C <sub>0</sub>		Allowable rotational speed <sup>(2)</sup> rpm	Assembled inner ring							
D <sub>2</sub>	L	B	H			Radial	Radial			Axial						
86.5	40	25.5	17	12	1	1	60	60	75	59	47 500	41 400	103 000	89 700	4 000	LRT 506025

Notes:  
 (1) Minimum allowable value of chamfer dimension r.  
 (2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.  
 Remark 1: The outer ring has an oil groove and an oil hole.  
 2: Grease is not prepacked. Perform proper lubrication.

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391052
Inside diameter	50 mm
Outside diameter	72 mm
Thickness	40 mm
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE