


GE Rod end SB65A-IKO - SB65A-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/sb65a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree α
			d	D	B	C	d_k	r_1 ⁽¹⁾ mm	
65	SB 65A	2.05	65	105	55	47	94	0.6	5
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N						
d_s Min.	Max. ⁽²⁾		D_s Min.	Max.					
69.5	76	433 000	100.5	87	2 600 000				

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391380
Inside diameter	65 mm
Outside diameter	105 mm
Thickness	55 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE