


GE Rod end SB75A-IKO - SB75A-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/sb75a-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree α	
			d	D	B	C	d_k ⁽¹⁾		
75	SB 75A	3.02	75	120	64	55	110	0.6	5
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N						
d_s	D_s		C_d	C_s					
Min. Max. ⁽²⁾	Max. Min.	N	N						
79.5 89.5	115.5 102	593 000	3 560 000						

Notes ⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391427
Inside diameter	75 mm
Outside diameter	120 mm
Thickness	64 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE