

GE Rod end SB85A-IKO - SB85A-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/sb85a-iko>

SPHERICAL BUSHINGS
steel Spherical Bushings



Identification number	Mass (Ref.) kg	Boundary dimensions mm						Per titl c
		d	D	B	C	d _k	r _{s min} (°)	
SB 85A	4,28	85	135	74	63	125	0.6	

Mounting dimensions mm			Dynamic load capacity C _d	Static load capacity C _s
Max. (°)	Max.	Min.		
100.5	130.5	116	772 000	4 630 000

Minimum allowable value of chamfer dimensions r₁ and r₂
When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value.
The inner ring and the outer ring have an oil groove and two oil holes, respectively.
Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391465
Inside diameter	85 mm
Outside diameter	135 mm
Thickness	74 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE