


**GE Rod end**  
**SB9014076-IKO - SB9014076-IKO**

<https://www.123bearing.eu/bearing-housing/rod-end/ge/sb9014076-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree $\alpha$
	SB	9014076		$d$	D	B	C	$d_k$	$r_1$ mm	
90	SB	9014076	4.71	90	140	76	65	130	0.6	5
Mounting dimensions mm				Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N					
$d_s$ Min.	$d_s$ Max. <sup>(1)</sup>	$D_s$ Min.	$D_s$ Max.							
94.5	105.5	135.5	121	829 000	4 970 000					

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

**PRODUCT FEATURES**

Brand	IKO
N° Ean13	3663952391496
Inside diameter	90 mm
Outside diameter	140 mm
Thickness	76 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE