

GE Rod end
SB130200110-IKO - SB130200110-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/sb130200110-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree α	
	d	D		B	C	d_k	r_1	r_2		
130	SB 130200110		13.8	130	200	110	95	185	1	5
Mounting dimensions mm				Dynamic load capacity C_d N	Static load capacity C_s N					
d_s	D_s									
Min.	Max. ⁽¹⁾	Min.								
135.5	148.5	194.5	171	1 720 000	10 300 000					

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r_1 and r_2 .
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391618
Inside diameter	130 mm
Outside diameter	200 mm
Thickness	110 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE