

## GE Rod end GE90ES-2RS-IKO - GE90ES-2RS-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/ge90es-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d <sub>s</sub>	r <sub>1</sub> <sup>(1)</sup> r <sub>1s</sub> min	r <sub>2</sub> <sup>(1)</sup> r <sub>2s</sub> min	α	α <sub>1</sub>	
<b>90</b>		<b>GE 90ES-2RS</b>	<b>2.82</b>	90	130	60	50	115	1	1	5	3	
Mounting dimensions mm		Dynamic load capacity C <sub>d</sub>		Static load capacity C <sub>s</sub>									
d <sub>s</sub>		D <sub>s</sub>		N		N							
Min.	Max. <sup>(2)</sup>	Max.	Min.										
95.5	98	124.5	112	564 000		3 380 000							

Notes<sup>(1)</sup> Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>s</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391939
Inside diameter	90 mm
Outside diameter	130 mm
Thickness	60 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE