

GE Rod end
GE140ES-2RS-IKO - GE140ES-2RS-IKO
<https://www.123bearing.eu/bearing-housing/rod-end/ge/ge140es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1	
140	GE 140ES-2RS		11.4	140	210	90	70	180	1	1	7	5	
Mounting dimensions mm		Dynamic load capacity C_d N	Static load capacity C_s N	d_s		D_s							
Min.	Max.(2)			Max.	Min.	Max.	Min.	Max.					
145.5	155.5	204.5	176	1 240 000									

Notes(1)
(1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392011
Inside diameter	140 mm
Outside diameter	210 mm
Thickness	90 mm
Type	GE
Weight	11127 g
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE