

GE Rod end GE110GS-IKO - GE110GS-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/ge110gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α ₁
110	GE 110GS		9.70	110	180	100	70	160	1	1	12	11
Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N	d _s		D _s						
Min.	Max.(2)			Max.	Min.	Max.	Min.	Max.				
115.5	124.5	174.5	154	1 100 000		6 590 000						

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392516
Inside diameter	110 mm
Inside diameter	4.331" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	100 mm
Thickness	3.937" inch
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE