

GE Rod end GE140GS-IKO - GE140GS-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/ge140gs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree			
	Without seals	With seals		d	D	B	C	d _s	r ₁ ⁽¹⁾	r ₂ ⁽¹⁾	α	α ₁	
140	GE 140GS		19.2	140	230	130	80	200	1	1	16	15	
Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N	d _s		D _s							
Min.	Max. ⁽²⁾			Max.	Min.	Max.	Min.	Max.					
145.5	152	224.5	195	1 570 000									

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392554
Inside diameter	140 mm
Inside diameter	5.512" inch
Outside diameter	230 mm
Outside diameter	9.055" inch
Thickness	130 mm
Thickness	5.118" inch
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE