


GE Rod end GE200GS-2RS-IKO - GE200GS-2RS-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/ge200gs-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		d	D	B	C	d _s	r ₁ (1)	r ₂ (1)	α	α ₁
200	GE 200GS-2RS		43.9	200	320	165	100	275	1.1	1.1	15	14
Mounting dimensions mm			Dynamic load capacity C _d N	Static load capacity C _s N								
d _s		D _s										
Min.	Max.(2)	Max.	Min.									
207	220	313	289	2 700 000		16 200 000						

Notes (1) Minimum allowable value of chamfer dimensions r₁ and r₂.
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392615
Inside diameter	200 mm
Inside diameter	7.874" inch
Outside diameter	320 mm
Outside diameter	12.598" inch
Thickness	165 mm
Thickness	6.496" inch
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE