


## GE Rod end GE240GS-2RS-IKO - GE240GS-2RS-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/ge240gs-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
<b>240</b>		<b>GE 240GS-2RS</b>	<b>66,1</b>	<b>240</b>	<b>370</b>	<b>190</b>	<b>110</b>	<b>325</b>	<b>1,1</b>	<b>1,1</b>	<b>15</b>	<b>14</b>
Mounting dimensions mm		Dynamic load capacity $C_d$		Static load capacity $C_s$								
$d_s$		$D_s$		N		N						
Min.	Max.(2)	Max.	Min.									
<b>247</b>	<b>263,5</b>	<b>363</b>	<b>320</b>	<b>3 510 000</b>		<b>21 000 000</b>						

Notes(1)  
(1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392653
Inside diameter	240 mm
Outside diameter	370 mm
Thickness	190 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE