


## GE Rod end SBB60-2RS-IKO - SBB60-2RS-IKO

<https://www.123bearing.eu/bearing-housing/rod-end/ge/sbb60-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) kg	Boundary dimensions mm(inch)			
	Without seal	With seals		d	D	B	C
<b>95.250</b> (3 7/8)		<b>SBB 60-2RS</b>	<b>6.67</b>	95.250 (3 7/8)	149.225 (5 7/8)	83.34 (3.281)	71.42 (2.812)
d <sub>k</sub>	Radial internal clearance mm Min./Max.	Mounting dimensions mm d <sub>1</sub> r <sub>1</sub> max. r <sub>2</sub> max.		Dynamic load capacity C <sub>d</sub> N	Static load capacity C <sub>s</sub> N		
137 (5.394)	0.13 / 0.23	108.4	0.6 0.8	960 000	5 760 000		

Notes: (1) Minimum allowable value of chamfer dimensions r<sub>1</sub> and r<sub>2</sub>.  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d<sub>k</sub>.  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952392998
Inside diameter	95.25 mm
Outside diameter	149.225 mm
Thickness	83.34 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE