


Yoke type track roller CRY22-V-IKO - CRY22-V-IKO

<https://www.123bearing.eu/bearing-housing/roller-bearing/yoke-track-roller/cry22-v-iko>

IKO
ROLLER FOLLOWERS
Non-separable Roller Followers, Inch Series **Full Complement Type /With Inner Ring**



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions: mm(inch)									
	Shield type Cylindrical outer ring	Sealed type Cylindrical outer ring		d	D	B	C						
9.525 (3/8)	CRY 22 V		136	9.525 $^{+0.001}$	34.925 $^{+0.001}$	20.638(0.8125)	19.050 $^{+0.001}$						
				Shaft dia.				Basic dynamic load rating C	Basic static load rating C ₀				
				Push fit		Drive fit				Press fit			
				Min.	Max.	Min.	Max.	Min.	Max.	N	N		
				25.0(0.984)	1.588 (1/16)	9.507	9.517	9.523	9.533	9.528	9.538	23 600	31 700

Remarks: 1. The inner ring has an oil hole.
2. Provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952398099
Inside diameter	9.525 mm
Inside diameter	3/8" inch
Outside diameter	34.925 mm
Outside diameter	1 3/8" inch
Thickness	20.638 mm
Thickness	13/16" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE